Pfister

## Pfirst Series™
Pull-Out Kitchen Faucet

G133-10CC Finish*(CC)* ❑
G133-10SS Finish*(SS)* ❑
G133-10WW Finish*(WW)* ❑
G133-10YY Finish*(YY)* ❑

- Single Control
- 1 or 3-Hole Installation
- Pforever Seal

Specifications

Features

- 1.8 GPM Flow Rate
- 1 or 3-Hole Installation; Deck Plate or Single Hole Mounting Option
- Two Function Pull-Out Spray
- Pforever Seal Ceramic Disc Valve
- Pforever Warranty®

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- NSF 61/9 Annex G (Low lead)
- CEC Compliant
- Cal Green Compliant
- ADA Compliant-ANSI A117.1 (Lever handles only)
- ASME A112.18.3 (Backflow Prevention)

Dimensions

8-23/32 [221.2]

2-1/8 [54]

2-7/16 [62]

Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings

9-7/8 [250.6]

8-5/8 [219.3]

6-11/32 [160.9]

2-1/4 [57.2] MAX DECK THICKNESS

9-15/16 [252.4]

11/32 [9]

7-7/8 [200]

10 [254]

Optional Deckplate