

# 16351-W

20 Amp Decora Plus Single Receptacle/Outlet, Commercial Grade, Self-Grounding

Decora Plus Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White



Color :  White

UPC Code : 078477473863

Country Of Origin : Please Contact Customer Service.

RoHS Compliant : Yes

NEMA :  5-20R

Available Colors :



## Technical Information

AC Horsepower Ratings

**At Rated Voltage** : 1 HP

Electrical Specifications

**Amperage** : 20 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** : Withstands 2000V per UL498

**Grounding** : Self-Grounding

**Pole** : 2

**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current

**Voltage** : 125 VAC

**Wire** : 3

Environmental Specifications

**Flammability** : Rated V-2 per UL 94

**Operating Temperature** : -40°C to 60°C

Material Specifications

**Body Material** : Thermoplastic Nylon

**Clamp Nuts** : Zinc-Plated Steel

**Face Material** : Thermoplastic Nylon

**Ground Clips** : Brass-Plated

**Grounding Screw** : Brass 8-32

**Line Contacts** : Brass Triple-Wipe .031 Thick

**Terminal Screws** : Brass 10-32

**Yoke** : Zinc-Plated Steel

Mechanical Specifications

**Product ID** : Ratings are permanently marked on device

**Screw Terminal Torque** : 14-18 in-lbs

**Terminal Accom.** : 14-10 AWG

**Terminal ID** : Brass-Hot, Green-Ground, White-Neutral

**Termination** : Back or Side Wire

Product Features

**Amperage** : 20 A

**Body Material** : Thermoplastic Nylon

**Brand** : Decora Plus

**Color** : White

**Device Type** : Single Receptacle Outlet

**Face Material** : Thermoplastic Nylon

**Feature 4** : Smooth Face

**Grade** : Commercial Specification Grade

**Grounding** : Self-Grounding

**NEMA** : 5-20R

**Pole** : 2

**Standards and Certifications** : UL

**Strap Material** : Steel

**Termination** : Back or Side Wire

**Voltage** : 125 VAC

**Warranty** : 10-Year Limited

**Wire** : 3

Standards and Certifications

**ANSI** : C-73

**NEMA** : WD-6

**NOM** : 057

**UL498** : File E13399

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2023 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)